



LED T8 TUBE

Designed to illuminate large linear areas of workspace using the lowest power consumption, the LED T8 tube is the best solution for high usage conveniences and general lighting attempts. The fixture is ideal for maximum maintained light output applications and reduces maintenance costs by extending the relamping cycle.

Features and Benefits

- 5 Years warranty
- UL, RoHs and CE certification
- Simple installation
- Large opening angle 190°
- Field angle 300°



single bi-pin
ZL42WT850KUL

Applications

- Entrances areas and country yards
- Offices
- Supermarkets
- Walkways & parking lots
- Factories and warehouses
- Shops



G13 (medium bi-pin)
ZLT8041540
ZLT8041550
ZLT8041565


LED T8 TUBE KIT



ZLKITT8120



Color Temperature



Technical Parameters

Product Code	Watts	Base	Length	Lumens	Voltage	Beam out angle	Life time	Color Temperature	CRI	Dimmable	Warranty	Certificates
ZLT8041540	15.5W	G13	120cm	1800lm	100-277V	190°	50,000 hrs	4000K	>80Ra	No Dim	5 year	UL / ROHS
ZLT8041550	15.5W	G13	120cm	1800lm	100-277V	190°	50,000 hrs	5000K	>80Ra	No Dim	5 year	UL / ROHS
ZLT8041565	15.5W	G13	120cm	1800lm	100-277V	190°	50,000 hrs	6500K	>80Ra	No Dim	5 year	UL / ROHS
ZL42WT850KUL	42W	1 Pin	240cm	5500lm	100-277V	190°	50,000 hrs	5000K	>80Ra	No Dim	5 year	UL

ZLKITT8120 Fixture for LDITA tube, 120cm, base G13, connetion single input type B, certification C E.

For installation and safety notes visit: www.zolulighting.com