



LED Linear High Bay IP65 ETL

Zolu Lighting LED Linear High Bay was specially designed to provide a much larger surface area for heat dissipation and a perfect homogeneous lighting distribution. They are ideal for most commercial applications, such as supermarket, parkings, workshops, toll-gate, gas stations, exhibition hall, municipal engineering and other lighting areas.

Features and applications


- Excellent heat dissipation performance
Input voltage is AC100-277V, making more convenient of the installation and usage.
- Fast Installation
Long lifetime due to high quality LED chips and drivers
- 5 Years warranty
- ETL Certificate
- Different Color Temperature Available (3000k,4000k, 5000k)
- Operating Ambient Temperature -40°~+50°C
- Perfectly suitable for industrial use due to IP65
- No UV or IR and completely mercury free
- Dimmable 0-10V and DALI available.



Mounting accessories included.



Optional Emergency Power supply up to 90 minutes upon request.



Technical Parameters

Product Code	Watts	Size	Lumens	CCT	Input Voltage	Power Factor	Beam Angle	CRI	Life Span	IP	Warranty	Certificates
ZL60WLHB06M50KUIP65	60W	605*135*72mm	8400lm	5000K	AC100-277V	>0.90	120°	Ra≥70	50,000 hrs	IP65	5 years	ETL
ZL100WLHB06M50KUIP65	100W	605*135*72mm	14000lm	5000K	AC100-277V	>0.90	120°	Ra≥70	50,000 hrs	IP65	5 years	ETL
ZL150WLHB09M50KUIP65	150W	905*135*72mm	21000lm	5000K	AC100-277V	>0.90	120°	Ra≥70	50,000 hrs	IP65	5 years	ETL
ZL200WLHB12M50KUIP65	200W	1205*135*72mm	28000lm	5000K	AC100-277V	>0.90	120°	Ra≥70	50,000 hrs	IP65	5 years	ETL