



The ideal solution for production areas, parking lots, gardens, and other places where harsh conditions have to be counteracted. Thanks to its polycarbonate shell casted from a single mold and its massive internal aluminum core, the fixture is completely dust/waterproof, great stability, and assures good thermal conditions. The removable end caps housing the connection terminals allow quick and easy installation as well as maintenance. The LED Linear Light IP69K may function as a single accessory fixture or in a continuous line setting.


LED Linear Light IP69K

Features and benefits

- Zolu Lighting quality and reliability
- IP69K suitable for damp locations
- IK10 protection, shatterproof design - up to 50,000hrs lifespan
- Single installation or continuous line setting
- Highly energy efficient - up to 130lm/W
- High luminous flux - up to 14,300lm
- Isolated power driver
- No UV or IR and completely mercury free
- Working temperature -30 -+50 °C

Applications




- Factories and production areas
- parkings, corridors, storage and loading areas, etc



Technical specifications

Product code	Power	Light output	CCT	Finish	Dimensions
ZL30WLL06MX50K	30W	3900lm	5000K	White	560x72x78mm
ZL40WLL12MX40KUL	40W	5400lm	4000K	White	1170x72x78mm
ZL40WLL12MX40KUL-BK	40W	5400lm	4000K	Black	1170x72x78mm
ZL60WLL12MX40KUL	60W	7800lm	4000K	White	1170x72x78mm
ZL60WLL12MX50KUL	60W	7800lm	5000K	White	1170x72x78mm
ZL60WLL12MX50KUL-BK	60W	7800lm	5000K	Black	1170x72x78mm
ZL80WLL24MX50KUL	80W	10800lm	5000K	White	2370x72x78mm
ZL110WLL24MX50KUL	110W	14300lm	5000K	White	2370x72x78mm

- **X** stands for Dimmable option. When **X** is **D**, stands for **0-10V** dimmable. Blank stands for non dimmable.
- **NOTE:** The addition of **-EB** at the end of the code, stands for Emergency Battery. 15W, 90min.
- **NOTE:** The addition of **-DALI** at the end of the code, stands for DALI Driver.
- **BK** at the end of the code, stands for Matte Black finish color. (Available for some models)



Main voltage	AC100-277V 50/60Hz
Power factor	>0.9
Efficiency	130lm/W
Dimmable	0-10V optional
Ingress protection	IP69K suitable for damp locations
CRI	Ra>80
Housing	Single mold casted polycarbonate
Beam spread	120°
CCT	4000K / 5000K available
Certificates	UL / (CE / RoHS only on 30W model)
Warranty	5 Year