

ZOLU LIGHTING



Features and Benefits

- 5 years warranty
- Single installation
- High Luminous flux / up to 3536 Im
- No UV or IR and completely mercury free

can product general lighting as well as circulation lighting.

- Ambient temperatura 30 -+50 °C
- Dimmable 0-10V


Applications

- Receptions
- Work areas
- On desks
- Libraries





Color Temperature



Technical Parameters

Product Code \	Watts	Lumens	Voltage	Life Time	Color Temperature	CRI	Beam Angle	Dimension	Warranty	Certificates
ZL36W01LL4UD30KUL 3	36W	3536lm	100-277V	50000 hrs	3000k	>80Ra	1 10°	1219*50*80mm	5 years	CE / UL
ZL36W01LL4UD40KUL	36W	3536lm	100-277V	50000 hrs	4000K	>80Ra	1 1 0°	1219*50*80mm	5 years	CE / UL
ZL36W01LL4UD50KUL 3	36W	3536lm	100-277V	50000 hrs	5000K	>80Ra	1 1 0°	1219*50*80mm	5 years	CE / UL

EXTRAS

ZLSUSPENDKITLL01 Kit for suspendent installation, two units for kit.

ZLSUSPENDKITLL02 Union surface installation kit for two lamps, for single run and continuous.

ZLSURFACEKITLL Patch for linear led for interiors, two units for kit.

For installation and safety notes visit: www.zolulighting.com

