



## LED In-ground Light ETL

Equipped with one, two, or three light apertures to meet different lighting requirements, these luminaires designed to bear pressure loads from vehicles with pneumatic tires. The luminaires must not use for traffic lanes where they are subject to horizontal pressure from vehicles braking, accelerating, and changing direction. Exclusive features include Housing and trims made of Stainless Steel, frosted or clear glass, chromatic quality, energy efficiency, and superior visual comfort. Available in different LED color temperatures and RGB color changing options, letting designers and architects create the mood or lighting effects. Suitable for wet locations thanks to Protection class IP67.

### Features and Benefits


- Drive on and walk on capable
- 40°C to +85°C operating temperature
- Use standard prepipe for concrete
- IP67 Protection
- +50,000 hour lifespan
- Stainless steel housing
- Different style and color trim options
- 3 Year warranty



### Applications

- Concrete driveway, landscape, deck & step

### Color Temperature



### Technical Parameters

Product Code	Watts	Lumens	Voltage	Beam Angle	Dimension	Color Temperature	IP	Warranty	Certificates
ZL3WINXXKETL-***-##	3W	275lm	24 V	45°	44mm	2700/3000/4000/5000k	IP67	3 year	RoHS / ETL / CE
ZL3WINFXXKETL-***-##	3W	260lm	24 V	120°	44mm	2700/3000/4000/5000k/RGB/RGBW	IP67	3 year	RoHS / ETL / CE












- NOTE: XX Denote the color temperature, when is XX = 27 - 30 - 40 - 50 - RGB - RGBW, stands for 2700k - 3000k - 4000k - 5000k - RGB - RGBW
- \*\*\* Denote the trim style, when is \*\*\* = RDM - SQ or SQC - SC - 1WY - 2WY - 3WY, stands for Round - Square - Scoop - 1 Way - 2 Way - 3 Way
- ## Denote the trim color, when is ## = MS - MB - MW, stands for Matte Silver, Matte Black, Matte White

- NOTE: Driver not included.

Warranty based on 12 hours daily use

For installation and safety notes visit: [www.zolulighting.com](http://www.zolulighting.com)

### Ordering Guide

System Part	Image	Product	Product Code	Color Temperature / Trim Color
<b>Engine</b>		3W Light	ZL3WINXXKETL-***-##	2700k / 3000k / 4000k / 5000k
		Frosted 3W Light	ZL3WINFXXKETL-***-##	2700k / 3000k / 4000k / 5000k RGB / RGBW
<b>Trim</b>		Round Stainless Steel	-RDM	Matte Silver (MT) Matte Black (MB) Matte White (MW)
		Square Stainless Steel	-SQ	Matte Silver (MT) Matte Black (MB) Matte White (MW)
		Square Stainless Steel	-SQC	Matte Silver (MT) Matte Black (MB) Matte White (MW)
		Scoop Stainless Steel	-SC	Matte Silver (MT) Matte Black (MB) Matte White (MW)
		1 Way Stainless Steel	-1WY	Matte Silver (MT) Matte Black (MB) Matte White (MW)
		2 Way Stainless Steel	-2WY	Matte Silver (MT) Matte Black (MB) Matte White (MW)
		3 Way Stainless Steel	-3WY	Matte Silver (MT) Matte Black (MB) Matte White (MW)
	<b>Housing</b>		In-ground Housing	ZLINHOUSING-01
		Concrete Housing Not Included	ZLINHOUSING-02	Gray

• XX = Color Temperature / \*\*\* = Trim Style / ## = Trim Color.

For installation and safety notes visit: [www.zolulighting.com](http://www.zolulighting.com)