



LED Slim Troffer Light

The highly efficient LED Slim Troffer Light system provides optimal light uniformity while delivering high-performance efficacy up to 110 lumens per watt. All electrical components are UL approved, ETL approved for dry/damp location and flicking free. With energy savings of over 50% compared to fluorescent troffers coupled with a projected life of 50,000 hours, die-formed of 0.6mm cold-rolled steel body, steel surface painted after fabrication with high gloss backed white matte powder paint, the high-diffusion light-milky acrylic diffuser and, the Recessed or Suspended installation options, makes it a perfect balance of stylish aesthetics, unbeatable energy savings, exceptional performance and ideal for most commercial applications.



Features and Benefits

- UL, ETL and DLC Certificate
- 5 Year Warranty
- >80 CRI
- Recessed or suspended installation
- High luminous efficacy 110 lm/w
- Working temperature: -4°F~104°F
- Flicking free

Applications

- Supermarket, parking workshop, toll-gate, gasoline station, exhibition hall, municipal engineering and other lighting area.

Color Temperature



Technical Parameters

Product Code	Watts	Lumens	Voltage	Dimensions	Life Time	Color Temperature	CRI	Warranty	Certificates
ZL36WS02TF1D30K	36W	3960lm	120-277 V	1x4 (47.6"x12"x3.15")	50,000 hrs	3000K	>80	5 year	UL / ETL / DLC
ZL36WS02TF1D40K	36W	3960lm	120-277 V	1x4 (47.6"x12"x3.15")	50,000 hrs	4000K	>80	5 year	UL / ETL / DLC
ZL36WS02TF1D50K	36W	3960lm	120-277 V	1x4 (47.6"x12"x3.15")	50,000 hrs	5000K	>80	5 year	UL / ETL / DLC
ZL36WS02TF2D30K	36W	3960lm	120-277 V	2x2 (23.8"x23.8"x3.15")	50,000 hrs	3000K	>80	5 year	UL / ETL / DLC
ZL36WS02TF2D40K	36W	3960lm	120-277 V	2x2 (23.8"x23.8"x3.15")	50,000 hrs	4000K	>80	5 year	UL / ETL / DLC
ZL36WS02TF2D50K	36W	3960lm	120-277 V	2x2 (23.8"x23.8"x3.15")	50,000 hrs	5000K	>80	5 year	UL / ETL / DLC
ZL50WS02TF4D30K	50W	5500lm	120-277 V	2x4 (47.6"x23.8"x3.15")	50,000 hrs	3000K	>80	5 year	UL / ETL / DLC
ZL50WS02TF4D40K	50W	5500lm	120-277 V	2x4 (47.6"x23.8"x3.15")	50,000 hrs	4000K	>80	5 year	UL / ETL / DLC
ZL50WS02TF4D50K	50W	5500lm	120-277 V	2x4 (47.6"x23.8"x3.15")	50,000 hrs	5000K	>80	5 year	UL / ETL / DLC

• NOTE: Available for dimmable version, for emergency version or for installing with sensor, upon special request.

Warranty based on 12 hours daily use

For installation and safety notes visit: www.zolulighting.com