



The product brings the energy efficiency and long-life benefits of LED to HID replacement and provides instant savings. The Zolu Lighting LED T-shapes are directional and deliver maximum lumens on the floor, with the right lamp size and light distribution, it can easily deliver over 60% energy savings and has a rated life of 50,000 hours – 3 times longer than traditional HID lamps–. The plastic lens helps to minimize glare and increase overall lamp performance, which results in a high-quality lighting experience for any applications.

## LED HID T-Shape

### Features and benefits

- Zolu Lighting quality and reliability
- Shatter resistant
- 50,000hrs helps minimize replacement and maintenance costs
- An isolated driver helps with heat dissipation
- 6Kv surge protection

### Applications

- Parking lots, warehouse, roadways
- Landscape lighting and showrooms

### Technical specifications

| Product code | Power | Light output | CCT   | Base |
|--------------|-------|--------------|-------|------|
| ZLHID10040   | 25W   | 3750lm       | 4000K | E26  |
| ZLHID10050   | 25W   | 3750lm       | 5000K | E26  |
| ZLHID15040   | 40W   | 5850lm       | 4000K | E26* |
| ZLHID15050   | 40W   | 5850lm       | 5000K | E26* |
| ZLHID17550   | 65W   | 9900lm       | 5000K | E39  |
| ZLHID25050   | 90W   | 13600lm      | 5000K | E39  |

\* Includes E26 to E39 adapter

- The LED HID Series is wet location rated, when exposed to water use ONLY with device base up.
- Apporved for totally enclosed high bay and low bay fixtures with a minimum lamp compartment of 16 inches in diameter by 10.43 inches high.
- Bypass construction.
- NON dimmable.



|                             |            |
|-----------------------------|------------|
| <b>Main voltage</b>         | 100-277V   |
| <b>Input line frequency</b> | 50/60HZ    |
| <b>Min. starting temp</b>   | -30°C      |
| <b>Max. operating temp</b>  | 45°C       |
| <b>CRI</b>                  | Ra≥80      |
| <b>Lens angle</b>           | 180°       |
| <b>Lamp life (rated)</b>    | 50,000 hrs |
| <b>Certificates</b>         | UL         |
| <b>Warranty</b>             | 5 Year     |

